





			Spoke Count		RRP	Weight	Spoke Length	
					£	g	NDS / DS	
27.5"	 6 Bolt	Front	32H	PRO 5 Front Standard 100mm	190	824	273 / 275	
				PRO 5 Front Boost 110mm	190	830	273 / 275	
		Rear	32H	PRO 5 Rear Standard 135mm / 142mm	310	950	275 / 273	
				PRO 5 Rear Boost 148mm	310	953	275 / 273	
					PRO 5 Rear Single Speed / Trials	320	1103	275 / 275
	 Centrelock	Front	32H	PRO 5 CL Front Standard 100mm	190	790	275 / 277	
				PRO 5 CL Front Boost 110mm	190	795	275 / 277	
		Rear	32H	PRO 5 CL Rear Standard 135mm / 142mm	310	920	275 / 273	
PRO 5 CL Rear Boost 148mm				310	923	275 / 273		

			Spoke Count		RRP	Weight	Spoke Length	
					£	g	NDS / DS	
29"	 6 Bolt	Front	32H	PRO 5 Front Standard 100mm	190	868	292 / 295	
				PRO 5 Front Boost 110mm	190	874	292 / 295	
		Rear	32H	PRO 5 Rear Standard 135mm / 142mm	310	995	295 / 292	
				PRO 5 Rear Boost 148mm	310	998	295 / 292	
					PRO 5 Rear Single Speed / Trials	320	1140	293 / 293
	 Centrelock	Front	32H	PRO 5 CL Front Standard 100mm	190	833	294 / 295	
				PRO 5 CL Front Boost 110mm	190	840	294 / 295	
		Rear	32H	PRO 5 CL Rear Standard 135mm / 142mm	310	965	295 / 292	
PRO 5 CL Rear Boost 148mm				310	968	295 / 292		

## RIM ONLY

Rim DIA.	Part number	Description	RRP	Weight	ERD
			£	g	mm
27.5"	WHSP064	FORTUS 23 32H Black	110.00	420	566
29"	WHSP065	FORTUS 23 32H Black	110.00	450	604

- › Fortus 23mm Front Standard and Boost wheels come supplied with 15mm endcaps.
- › Fortus 23mm Rear Standard wheels come supplied with 142 x 12mm endcaps.
- › Fortus 23mm Rear Boost wheels come supplied with 148 x 12mm endcaps.

Hubs are available in seven anodised colours: Red, Orange, Blue, Purple, Silver, Black, Bronze.



Recommended tyre width: 2.0" - 2.35"



Recommended maximum pressure: 55 PSI / 4.1 Bar

